



Prevedenie	Clamping Range Double Seal Ømin-max	Clamping Range Outer Seal Ømin-max	TL mm	TD mm	E mm	HD mm	SW Cap mm	SW Body mm	D mm	max. H mm	Obj. číslo RAL 7035 sivá	Obj. číslo RAL 7001 šedá	Obj. číslo RAL 9005 čierna	Balné množstvo
M16	3,0 - 7,0	5,0 - 10,0	9.0	16.000	0,5 - 4,0	16,2 - 16,4	22	22	26.5	42.4	BMOS-DS-11	BMOS-DS-01	BMOS-DS-21	100
M20	3,0 - 7,0	6,0 - 12,0	9.0	20.000	0,5 - 4,0	20,2 - 20,4	24	24	30.3	41.5	BMOS-DS-12	BMOS-DS-02	BMOS-DS-22	50
M20	3,0 - 7,0	7,0 - 13,0	9.0	20.000	0,5 - 4,0	20,2 - 20,4	25	25	30.3	42.1	BMOS-EU-DS-12	BMOS-EU-DS-02	BMOS-EU-DS-22	50
M25	8,0 - 13,0	11,0 - 17,0	9.0	25.000	0,5 - 4,0	25,2 - 25,4	29	29	36.3	43.7	BMOS-EU-DS-13	BMOS-EU-DS-03	BMOS-EU-DS-23	25
M32	11,0 - 16,0	15,0 - 21,0	9.0	32.000	0,5 - 4,0	32,2 - 32,4	36	36	43.2	50.1	BMOS-EU-DS-14	BMOS-EU-DS-04	BMOS-EU-DS-24	25

